

SKID STEERS

■ 2054 ■



mustangmfg.com

PREPARE to dig, load and haul



- Operating capacity of 1,750 lbs. with optional counterweight provides exceptional lifting and loading capabilities.

- Breakout forces up to 5,000 lbs. provide extra muscle for tough jobs.



- Three different control configurations, including dual lever with foot controls, dual lever with hand controls, and T-bar with hand controls.

- A wide variety of attachments are powered by strong, auxiliary hydraulics with standard flat-faced couplers.
- Sturdy Level II-certified ROPS/FOPS structure provides protection, yet allows an unobstructed view to the attachment and surrounding work areas.



West Bend, WI USA
Tel: 262-334-9461
Fax: 262-338-7517

For more information on Mustang equipment, call our literature hotline at **800-628-0491** or visit our website: **mustangmfg.com**

A Per SAE J818, SAE J732, and ISO 14397
B Unit weight with standard bucket, 175 lbs. (79 kg) operator and full fuel tank

SPECIFICATIONS

	2054	
DIMENSIONS	A. Overall Operating Height - Fully Raised (mm)	146.5" (3721)
	B. Height to Hinge Pin - Fully Raised (mm)	116" (2946)
	C. Overall Height to Top of ROPS (mm)	77.7" (1973)
	D. Ground Clearance to Chassis (mm)	7.8" (197)
	E. Overall Length with Bucket (mm)	125.5" (3188)
	F. Overall Length without Bucket (mm)	97" (2448)
	G. Wheelbase (mm)	38.5" (978)
	H. Dump Reach at Full Height (mm)	24" (610)
	I. Bucket Rollback at Ground	28°
	J. Dump Angle	34°
	K. Overall Width (mm)	60.7" (1542)
	L. Bucket Width (mm)	61.5" (1562)
	M. Clearance Circle - Rear (mm)	59.3" (1506)
	N. Clearance Circle - Front without Bucket (mm)	45.8" (1162)
	O. Clearance Circle - Front with Bucket (mm)	74.5" (1892)
	P. Seat to Ground Height (mm)	34.8" (884)
	Q. Rollback at Full Height	100°
	R. Dump Height (mm)	92" (2337)
	S. Departure Angle	26°
Standard Specification Tire Size	10.00x16.5 HD	
ENGINE	Make	Yanmar
	Model	4TNV88-Tier III
	Power (kW) @ rpm	47 hp (35) @3000
	Displacement (L)	133.6 cu.in. (2.19)
	Maximum Torque (Nm) @ rpm	106 ft.-lbs (145) @ 1680
HYDRAULIC SYSTEM	Auxiliary Hydraulics - Standard (L/min)	18 gpm (68.1)
	High-Flow Hydraulics - Optional (L/min)	28 gpm (106)
	Filtration	7 micron
	System Relief Pressure (bar)	2850 psi (197)
	Reservoir Capacity (L)	11.5 gal. (43.5)
CAPACITIES /WEIGHT	Rated Operating Capacity ^A (kg)	1650 lbs. (748)
	With Optional Counterweight ^A (kg)	1750 lbs. (794)
	Tipping Load (kg)	3300 lbs. (1497)
	Fuel Tank (L)	14.3 gal. (54.1)
	Travel Speed - Maximum (km/hr)	6.8 mph (10.9)
	Operating Weight ^B - Approximate (kg)	6080 lbs. (2758)

