

SKID STEERS

■ 2109 ■



mustangmfg.com

thoroughbred WORKHORSE



- Best in class skid steer provides high torque and high performance. It is among the industry's largest, most powerful skid steers.

- Faster ground speeds than any comparable machine, this skid steer will keep your projects on track and on time.



- True vertical-lift path design provides consistent forward reach throughout the entire 11'10" lift cycle.

- A ride control system option keeps operator energy high and avoids spilling loads by letting the lift arm "float," even at faster ground speeds.

- Just the right touch and feel makes operation intuitive. A special load-sensing pump pairs your application with the perfect hydraulic flow.



West Bend, WI USA
Tel: 262-334-9461
Fax: 262-338-7517

For more information on Mustang equipment, call our literature hotline at **800-628-0491** or visit our website: **mustangmfg.com**

A Per SAE J818, SAE J732, and ISO 14397
B Unit weight with standard bucket, 175 lbs. (79 kg) operator and full fuel tank

SPECIFICATIONS

		2109
DIMENSIONS	A. Overall Operating Height - Fully Raised (mm)	187.8" (4770)
	B. Height to Hinge Pin - Fully Raised (mm)	142" (3607)
	C. Overall Height to Top of ROPS (mm)	81" (2057)
	D. Ground Clearance to Chassis (mm)	9.1" (231)
	E. Overall Length with Bucket (mm)	161" (4089)
	F. Overall Length without Bucket (mm)	122" (3099)
	G. Wheelbase (mm)	55" (1397)
	H. Dump Reach at Full Height (mm)	38.2" (970)
	I. Bucket Rollback at Ground	28.5°
	J. Dump Angle	38°
	K. Overall Width (mm)	81" (2057)
	L. Bucket Width (mm)	84" (2134)
	M. Clearance Circle - Rear (mm)	80.5" (2045)
	N. Clearance Circle - Front without Bucket (mm)	60.6" (1539)
	O. Clearance Circle - Front with Bucket (mm)	102" (2583)
	P. Seat to Ground Height (mm)	41" (1041)
	Q. Rollback at Full Height	85°
	R. Dump Height (mm)	107" (2718)
	S. Departure Angle	21°
	Standard Specification Tire Size	14.00x17.5 HD
ENGINE	Make	Cummins
	Model	B4.5T-99C-Tier III
	Power (kW) @ rpm	99 hp (73.8) @ 2200
	Displacement (L)	275 cu.in. (4.5)
	Maximum Torque (Nm) @ rpm	305 ft.-lbs (414) @ 1500
HYDRAULIC SYSTEM	Auxiliary Hydraulics - Standard (L/min)	29 gpm (110)
	High-Flow Hydraulics - Optional (L/min)	41 gpm (155.2)
	Filtration	4 micron
	System Relief Pressure (bar)	3300 psi (207)
	Reservoir Capacity (L)	15 gal. (56.8)
CAPACITIES / WEIGHT	Rated Operating Capacity ^A (kg)	3850 lbs. (1747)
	Tipping Load (kg)	7700 lbs. (3493)
	Fuel Tank (L)	30.5 gal. (115)
	Travel Speed - Maximum (km/hr)	12.5 mph (20)
	Operating Weight ^B - Approximate (kg)	10,520 lbs. (4772)

REFERENCE DIAGRAMS

